

PERFORMANCE
EPOXY-COAT®
Transferrable Lifetime Warranties

9-22-21

POLY 200
Installation Instructions



MONDAY-FRIDAY 9-5PM
Tech Support Saturday 11-3PM EST
(800) 841-5580 EST

www.epoxy-coat.com

POLY 200 INSTRUCTIONS WARNING!

Please use your PPE (personal protection equipment). Proper ventilation is required for use. See the SDS sheet for more information, available at epoxy-coat.com.

Coverage at approximately 4 MILS.

.5 Gallon-	166 sq. ft
.75 Gallon-	250 sq. ft
1-gallon-	325 sq. ft
5 gallons-	1,600 sq. ft
55-gallon drum-	18,250 sq. ft

*DO NOT APPLY LESS THAN RECOMMENDED COVERAGE OR POLY 200 WILL NOT CURE CORRECTLY AND HAVE AN UNEVEN SURFACE.

Mixing is not required. Application is best in the morning or evening. Do not apply product in direct sunlight.

___ Step 1:

Open container, and pour contents into paint tray, with a 3/8 nap roller, roll all Poly200 on the floor.

___ Step 2:

Being sure to have a steady consistency with rolling application. Starting from the back of the room to the exit.

Application notes:

This product is applied very thin, 3-5mils only. If you are splitting the product, be sure to pour desired amount in paint tray. Then seal lid to be able to use the product at a later date.

** Dispose of contents/container in accordance with County/ State/ Federal laws and regulations

Fill out and return for warranty coverage.

Mail to: Certified Performance Coatings • 169 North Gratiot • Mt. Clemens, MI 48043 • Phone: (800) 841-5580 • Fax: (586) 468-8440 regulations.

<p>CERTIFIED PERFORMANCE COATINGS® <small>Transferrable Lifetime Warranties</small></p>	 <p><i>Warranty Certificate</i> 169 N. Gratiot • Mt. Clemens, MI 48043</p>	
Name: _____		
Address: _____ _____		
Email: _____		
Phone: _____		
Purchase Date: _____		Purchase Location: _____